



GREAT INT'L HOLDINGS LIMITED (22.5 series)

No.	Wheel size	Rim thickness	Disk thickness	Parameters					Vent Hole	TYRE	Valves	Remark
				P.C.D.	Bolt Hole	Center Hole	Bolt type	Offset				
01	22.5x8.25	7	14	φ275	8-φ24	φ221	1x45°	169	8-φ64	11R22.5	V3-20-4	
02	22.5x8.25	6	14	φ275	8-φ24	φ221	1x45°	169	8-φ64	11R22.5	V3-20-4	
03	22.5x8.25	7	14	φ275	8-φ27	φ221	SR18	169	8-φ64	11R22.5	V3-20-4	
04	22.5x8.25	6	14	φ275	8-φ27	φ221	SR18	169	8-φ64	11R22.5	V3-20-4	
05	22.5x8.25	7	14	φ275	8-φ32	φ214	SR22	169	8-φ64	11R22.5	V3-20-4	
06	22.5x8.25	7	16	φ275	8-φ32	φ214	SR22	169	8-φ64	11R22.5	V3-20-4	
07	22.5x8.25	6	14	φ275	8-φ32	φ214	SR22	169	8-φ64	11R22.5	V3-20-4	
08	22.5x8.25	7	14	φ285	8-φ32	φ221	SR22	169	8-φ64	11R22.5	V3-20-4	
09	22.5x8.25	7	16	φ285	8-φ32	φ221	SR22	169	8-φ64	11R22.5	V3-20-4	
10	22.5x8.25	7	14	φ285	8-φ32	φ221	SR22	165	6-φ73	11R22.5	V3-20-4	
11	22.5x8.25	8	16	φ285	8-φ32	φ221	SR22	169	8-φ64	11R22.5	V3-20-4	
12	22.5x8.25	7	14	φ285	8-φ32	φ221	SR22	169	pear	11R22.5	V3-20-4	
13	22.5x8.25	7	16	φ285	8-φ32	φ221	SR22	169	pear	11R22.5	V3-20-4	
14	22.5x8.25	6	14	φ285	8-φ32	φ221	SR22	169	8-φ64	11R22.5	V3-20-4	
15	22.5x8.25	7	14	φ285.75	10-φ26	φ220	1x45°	169	10-φ64	11R22.5	V3-20-4	
16	22.5x8.25	7	16	φ285.75	10-φ26	φ220	1x45°	169	10-φ64	11R22.5	V3-20-4	
17	22.5x8.25	8	16	φ285.75	10-φ26	φ220	1x45°	169	10-φ64	11R22.5	V3-20-4	
18	22.5x8.25	6	11	φ285.75	10-φ26	φ220	1x45°	168	2-108x76	11R22.5	V3-20-4	
19	22.5x8.25	7	14	φ285.75	10-φ26	φ220	1x45°	168	5-104x69	11R22.5	V3-20-4	
20	22.5x8.25	6	14	φ285.75	10-φ26	φ220	1x45°	169	10-φ64	11R22.5	V3-20-4	
21	22.5x8.25	7	14	φ285.75	10-φ32	φ222	SR22	169	10-φ64	11R22.5	V3-20-4	
22	22.5x8.25	7	16	φ285.75	10-φ32	φ222	SR22	169	10-φ64	11R22.5	V3-20-4	
23	22.5x8.25	7	14	φ285.75	10-φ32	φ222	SR22	169	6-φ73	11R22.5	V3-20-4	
24	22.5x8.25	8	16	φ285.75	10-φ32	φ222	SR22	169	10-φ64	11R22.5	V3-20-4	
25	22.5x8.25	7	14	φ285.75	10-φ32	φ222	SR22	169	Pear	11R22.5	V3-20-4	



GREAT INT'L HOLDINGS LIMITED (22.5 series)

No.	Wheel size	Rim thickness	Disk thickness	Parameters					Vent Hole	TYRE	Valves	Remark
				P.C.D.	Bolt Hole	Center Hole	Bolt type	Offset				
01	22.5x9.00	7	14	φ275	8-φ24	φ221	1x45°	175	8-φ64	12R22.5	V3-20-6	
02	22.5x9.00	6	14	φ275	8-φ24	φ221	1x45°	175	8-φ64	12R22.5	V3-20-6	
03	22.5x9.00	7	14	φ275	8-φ32	φ214	SR22	175	8-φ64	12R22.5	V3-20-6	
04	22.5x9.00	6	14	φ275	8-φ32	φ214	SR22	175	8-φ64	12R22.5	V3-20-6	
05	22.5x9.00	7	14	φ285	8-φ32	φ221	SR22	175	8-φ64	12R22.5	V3-20-6	
06	22.5x9.00	7	16	φ285	8-φ32	φ221	SR22	175	8-φ64	12R22.5	V3-20-6	
07	22.5x9.00	7	14	φ285	8-φ32	φ221	SR22	175	6-φ73	12R22.5	V3-20-6	
08	22.5x9.00	8	16	φ285	8-φ32	φ221	SR22	175	8-φ64	12R22.5	V3-20-6	
09	22.5x9.00	7	14	φ285	8-φ32	φ221	SR22	175	pear	12R22.5	V3-20-6	
10	22.5x9.00	7	16	φ285	8-φ32	φ221	SR22	175	pear	12R22.5	V3-20-6	
11	22.5x9.00	6	14	φ285	8-φ32	φ221	SR22	175	8-φ64	12R22.5	V3-20-6	
12	22.5x9.00	7	14	φ285.75	10-φ26	φ220	1x45°	175	10-φ64	12R22.5	V3-20-6	
13	22.5x9.00	7	16	φ285.75	10-φ26	φ220	1x45°	175	10-φ64	12R22.5	V3-20-6	
14	22.5x9.00	8	16	φ285.75	10-φ26	φ220	1x45°	175	10-φ64	12R22.5	V3-20-6	
15	22.5x9.00	6	14	φ285.75	10-φ26	φ220	1x45°	175	10-φ64	12R22.5	V3-20-6	
16	22.5x9.00	7	14	φ285.75	10-φ32	φ222	SR22	175	10-φ64	12R22.5	V3-20-6	
17	22.5x9.00	7	16	φ285.75	10-φ32	φ222	SR22	175	10-φ64	12R22.5	V3-20-6	
18	22.5x9.00	8	16	φ285.75	10-φ32	φ222	SR22	175	10-φ64	12R22.5	V3-20-6	
19	22.5x9.00	7	14	φ285.75	10-φ32	φ222	SR22	175	pear	12R22.5	V3-20-6	
20	22.5x9.00	7	16	φ285.75	10-φ32	φ222	SR22	175	pear	12R22.5	V3-20-6	
21	22.5x9.00	6	14	φ285.75	10-φ32	φ222	SR22	175	10-φ64	12R22.5	V3-20-6	
22	22.5x9.00	7	14	φ335	10-φ26	φ281	1x45°	175	10-φ70	12R22.5	V3-20-6	
23	22.5x9.00	7	16	φ335	10-φ26	φ281	1x45°	175	10-φ70	12R22.5	V3-20-6	
24	22.5x9.00	8	16	φ335	10-φ26	φ281	1x45°	175	10-φ70	12R22.5	V3-20-6	
25	22.5x9.00	8	14	φ335	10-φ26	φ281	1x45°	175	10-φ70	12R22.5	V3-20-6	

